

参考調査項目表

調査地点				No.1																									
孔径 (長さ)	深度 (GL-m)	層厚 (m)	土質	φ 116			φ 86			φ 66			標準貫入試験			孔内 水平 載荷	サンプリング		室内土質試験										
				粘土	砂	砂礫	粘土	砂	砂礫	粘土	砂	砂礫	粘土	砂	砂礫		シンウー ル	デ'ニソン	土粒子 の 密度	湿潤 密度	粒度		含水比	液性 限界	塑性 限界	一軸 圧縮	三軸 圧縮	圧密	
Φ 66 40.55m	0.30	0.30	黄土								0.30		●																
	1.90	1.60	砂礫じりシルト								1.60		●																
	2.80	0.90	シルト混り砂									0.90			●														
		2.90	砂質礫										2.90				●												
	5.70																●												
	6.70	1.00	砂									1.00				●													
		1.90	砂礫じりシルト										2.70		●														
	8.60														●														
	9.40	0.80	粘性土												●														
		2.30	砂										4.80					●											
	11.70																	●											
	12.90	1.20	シルト混り砂															●											
	14.20	1.30	砂															●											
	14.90	0.70	シルト									0.70		●															
	15.30	0.40	砂										0.40		●														
	16.00	0.70	砂礫じりシルト										0.70		●														
		1.80	砂											1.80				●											
	17.80																	●											
		2.80	砂礫じりシルト											2.80		●													
	20.60														●														
		2.30	シルト混り砂														●												
	22.90																●												
	23.70	0.80	砂質シルト										0.80		●														
		2.90	砂											2.90				●											
	26.60																●												
		2.00	砂礫じりシルト											2.00		●													
	28.60														●														
		2.20	シルト混り砂															●											
30.80																	●												
	1.90	シルト混り砂											1.90				●												
32.70																	●												
														●															
														●															
														●															
														●															
														●															
														●															
														●															
														●															
														●															
														●															
														●															
														●															
														●															
														●															
														●															
														●															
														●															
														●															
														●															
														●															
														●															
														●															
														●															
														●															
														●															
														●															
														●															
														●															
														●															
														●															
														●															
														●															
														●															
														●															
														●															
														●															
														●															
														●															
														●															
														●															
														●															
														●															
														●															
														●															
														●															
														●															
														●															
														●															
														●															
														●															
														●															
														●															
														●															
														●															
														●															
														●															
														●															
														●															
														●															
														●															
														●															
														●															
														●															
														●															
														●															
														●															
														●															

参 考 調 査 項 目 表

調査地点				No.2～7																									
孔径 (長さ)	深度 (GL-m)	層厚 (m)	土質	φ 116			φ 86			φ 66			標準貫入試験			孔内 水平 載荷	サンプリング		室内土質試験										
				粘土	砂	砂礫	粘土	砂	砂礫	粘土	砂	砂礫	粘土	砂	砂礫		シンワール	デ'ニソン	土粒子 の 密度	湿潤 密度	粒度		含水比	液性 限界	塑性 限界	一軸 圧縮	三軸 圧縮	圧密	
Φ 66 40.55m	0.30	0.30	粘土		0.30																								
	1.90	1.60	砂混じりシルト	1.60										●				●	●		●	●	●	●	●		●		
	2.80	0.90	シルト混り砂		0.90										●				●		●								
		2.90	砂質礫			2.90										●													
	5.70																												
	6.70	1.00	砂		1.00											●			●		●								
		1.90	砂混じりシルト	2.70										●			●		●	●		●	●	●	●		●		
	8.60	0.80	粘性土											●				●	●		●	●	●	●		●			
	9.40			4.80										●															
	11.70	2.30	砂												●														
	12.90	1.20	シルト混り砂													●													
	14.20	1.30	砂													●													
	14.90	0.70	シルト	0.70										●															
	15.30	0.40	砂	0.40																									
	16.00	0.70	砂混じりシルト	0.70										●				●	●		●	●	●	●	●		●		
		1.80	砂		1.80										●														
	17.80															●			●		●								
		2.80	砂混じりシルト	2.80										●				●	●		●	●	●	●	●		●		
	20.60													●															
		2.30	シルト混り砂		2.30										●				●		●								
	22.90														●														
	23.70	0.80	砂質シルト	0.80										●				●	●		●	●	●	●	●		●		
		2.90	砂		2.90										●				●		●								
	26.60															●													
		2.00	砂混じりシルト	2.00										●				●	●		●	●	●	●	●		●		
	28.60													●															
		2.20	シルト混り礫		2.20											●													
30.80																													
	1.90	シルト混り砂		1.90										●				●		●									
32.70														●															
			7.85										●																
													●																
													●																
													●																
													●																
			シルト										●				●	●		●	●	●	●	●		●			
36.60													●																
													●																
													●																
40.55													●																
数量				19.15	16.30	5.10	0.00	0.00	0.00	0.00	0.00	0.00	21	15	5	1	1	7	15	8	7	8	15	8	8	8	0	8	

集 計

	φ 116			φ 86			φ 66			標準貫入試験			孔内 水平 載荷	サンプリング		土粒 子 密度	湿潤 密度	粒度		含水 比	液性 限界	塑性 限界	一軸 圧縮	三軸 圧縮	圧密	箇所
	粘土	砂	砂礫	粘土	砂	砂礫	粘土	砂	砂礫	粘土	砂	砂礫		シンワール	デニソン			ふるい	沈殿							
No.1	0.00	0.00	0.00	0.00	0.00	0.00	19.15	16.30	5.10	21	15	5	0	0	0	0	0	0	0	0	0	0	0	0	0	1箇所
No.2～7	19.15	16.30	5.10	0.00	0.00	0.00	0.00	0.00	0.00	21	15	5	1	1	7	15	8	7	8	15	8	8	8	0	8	6箇所
計	114.90	97.80	30.60	0.00	0.00	0.00	19.15	16.30	5.10	147	105	35	6	6	42	90	48	42	48	90	48	48	48	0	48	7箇所